

Model NSR55-BM Belt Misalignment Switch

Description

NSR55-BM Belt Misalignment Switches are designed to alarm and/or shut down a conveyor system in the event of belt drift and misalignment. They are mounted on both sides of the conveyor belt, with roller arm of the switch positioned 15 cm away from the belt. As the belt starts drifting into either side, it will first contact with the switch arm. Arm will roll without disrupting the belt. If belt continues to drift further the switch arm will rotate and actuate microswitches at specified angles.

The product is suitable for reliable long term usage in most industrial applications due to its durable design. Anti-static powder coated aluminium cast enclosure is resistant to corrosion. Shaft and arm mechanisms are made of stainless steel and all internal parts are metal cast. NSR55-BM series products do not require any maintenance.

The switch arm actuates the alarm switch at 15° angle. If the belt continues to drift and the switch arm rotates until 18°, the second microswitch will be actuated and the system will stop. Can be customized with both switches working at the same angle.

All models conform to CE (European Union) and EAC (Eurasian Customs Union) standards. Microswitches used in these products are VDE approved.

Technical Specifications

- Enclosure: Aluminium Casting
- Micro Switch Rating: 240 V 3A
- Output Signal: (2) SPDT Alarm and Stop
- Cable Entry: PG13,5
- Temperature Rating: -40°C to +80°C
- Contact Angles: 15° and 18°
- Max. Contact Angle: -90° / 90°
- Protection Class: IP65
- Enclosure Color: Red (RAL 3020)
- Weight: 1.15 kg
- Mounting Orientation: It is suitable for double-sided use.
- Mechanical Endurance: 300000 cycles
- Impact Rating: IK09 (EN 62262)
- Warranty Period: 24 Months

Options

- ATEX Zone 21 / Zone 22
- Bus Security Interface
- Custom Contact Angles
- Mounting Bracket
- Custom Arm Dimensions

Safety Standards

- Electrical Safety EN 60947
- Mechanical Safety EN 60204
- Outdoor Safety EN 60529
- Impact Resistance EN 62262

Certificates

CE EAC


Micro switches are VDE approved.



Model Specifications

Model	Alarm			Stop		
	NC	NO	Angle	NC	NO	Angle
NSR55-BM	1	1	15°	1	1	18°

Technical Drawing



Dimensions are in mm.